

# OTHELLO DIM 12W IP54 Ceiling Light

3000K 1115lm



Product Code: PXOTH123D



## Technical Specifications


Model	Voltage	Power	Power Factor	Lumen (±5%)	Beam Angle	CCT	Lifespan	CRI	Dimensions
12W	AC230V	12W	≥0.9	1115	120°	3000K	40000h	≥80	Ø250*48mm

## Driver Data Sheet


Driver Data	Dimmable
Input Rated Voltage	AC230V
Frequency	50Hz
Input Voltage	AC200-240V
Efficiency	≥88%
No Load Wattage	≤0.5W
Total Load Wattage	12W±1W
Power Factor	≥0.9
Rated Input Current	≤0.07A
Full Load Output Voltage	60-75V
Rated Output Current	150mA
Output Current Range	150mA±5%
Power Tolerance	±5%
Current Output Tolerance	±5%
Dimmer	Triac Dimmer
Dimming Range	8-100%
Short Circuit Protection	PASS
Over Voltage Protection	PASS
Over Temperature Protection	PASS
Withstand Voltage	AC3750V

## Fixture Compatibility

Rated Wattage	12W
Electrical Classification	II
Ingress Protection	IP54
Operating Temperature	-20°C~45°C
Operating Humidity	0~90%
Storage Temperature	-20°C~65°C



## Beam Angle



Prelux's Othello surface mounted ceiling light uses high lumen SMD LED's and a fire-rated Polycarbonate opal diffuser with an even light output. With it's IP54 waterproof structural design and 120° wide beam angle the Othello is an ideal solution for damp locations.

- Environment friendly, without Mercury or other hazardous substances
- Up to 70% energy saving compared to standard CFL
- Long lifetime of 40,000 hours
- Dimmable 8-100%
- 120° wide beam angle
- CCT: 3000K
- No UV/IR light